



High-temperature segmented thermoelectric oxide module using p-type $\text{Ca}_3\text{Co}_4\text{O}_9$ and n-type $\text{ZnAlO}/\text{CaMn}_{0.95}\text{Nb}_{0.05}\text{O}_3$ legs

Le, Thanh Hung; Van Nong, Ngo; Jeffrey Snyder, G.; Pryds, Nini; Linderorth, Søren

Publication date:
2012

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):

Le, T. H., Van Nong, N., Jeffrey Snyder, G., Pryds, N., & Linderorth, S. (2012). *High-temperature segmented thermoelectric oxide module using p-type $\text{Ca}_3\text{Co}_4\text{O}_9$ and n-type $\text{ZnAlO}/\text{CaMn}_{0.95}\text{Nb}_{0.05}\text{O}_3$ legs*. Abstract from 6th International Workshop on Advanced Materials Science and Nanotechnology, Ha Long City, Viet Nam.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

(CODE: MEP7-O6)

HIGH-TEMPERATURE SEGMENTED THERMOELECTRIC OXIDE MODULE USING *p*-TYPE $\text{Ca}_3\text{Co}_4\text{O}_9$ AND *n*-TYPE $\text{ZnAlO}/\text{CaMn}_{0.95}\text{Nb}_{0.05}\text{O}_3$ Legs

Le Thanh Hung¹, Ngo Van Nong¹, G. Jeffrey Snyder², Nini Pryds¹ and Søren Linderorth¹

¹Department of Energy Conversion and Storage, Technical University of Denmark, DTU Risø Campus,
4000 Roskilde, Denmark.

²Jet Propulsion Laboratory/California Institute of Technology, 4800 Oak Grove Drive, Pasadena CA 91109
USA

E-mail: lthh@dtu.dk

ABSTRACT

Thermoelectric (TE) power generator using TE materials which directly convert heat into electricity offers a viable environmental friendly technology for waste heat recovery. Recently, TE oxide modules have gained much attraction since they are composed of cheap materials and are stable at high temperatures up to 1200 K, where most the conventional TE materials based on alloys are often degraded over the time. In this report, oxide TE materials of *p*-type $\text{Ca}_3\text{Co}_4\text{O}_9$, *n*-types ZnAlO , and $\text{CaMn}_{0.95}\text{Nb}_{0.05}\text{O}_3$ were used to fabricate high temperature TE segmented modules. These oxide materials were prepared by solid-state reaction, followed by a spark plasma sintering technique, and their thermoelectric properties were characterized from 300 to 1200 K. The module performance was first investigated by numerical modeling using the experimental thermoelectric properties data as input parameters. In these calculations, the power generation characteristics were investigated in terms of various *n*-leg selections (ZnAlO , $\text{CaMn}_{0.95}\text{Nb}_{0.05}\text{O}_3$, and segmented $\text{ZnAlO}/\text{CaMn}_{0.95}\text{Nb}_{0.05}\text{O}_3$), while the *p*-leg $\text{Ca}_3\text{Co}_4\text{O}_9$ was fixed. Based on the model predication, several modules were fabricated, tested, and compared again with the theoretical calculations. The obtained results are discussed in details and also compared with other reported oxide modules.